

AVerVision Interactive Visualisers *In Touch With Tomorrow's Teaching*

June 2008



Product Name

AVerVision CP130

AVerVision CP150

AVerVision300AF

AVerVision SPC300

AVerVision SPB350

Type	Portable	Portable	Portable	Portable	Platform
Image Sensor	1/2" CMOS	1/2" CMOS	1/2" CMOS	1/2.5" CMOS	1/2.5" CMOS
Total Pixels	850K Pixels	3.2M Pixels	3.2M Pixels	3.2M Pixels	5M Pixels
Output Resolution	XGA (1024 x 768)	XGA (1024 x 768)	XGA (1024 x 768)	XGA (1024 x 768)	1920x1080
Lens	f1 = 9.6mm	f1 = 9.6mm	f1 = 9.6mm	f1 = 7.3~21.9mm	f1 = 6~60mm
Zoom	8X Digital Zoom	16X Total Zoom (2X AVerZoom + 8X Digital Zoom)	16X Total Zoom (2X AVerZoom + 8X Digital Zoom)	48X Total Zoom (3X Optical + 2X AVerZoom + 8X Digital Zoom)	160X Total Zoom (8X Optical + 2.5X AVerZoom + 8X Digital Zoom)
Frame Rate	12fps (Max.)	24fps (Max.)	24fps (Max.)	24fps (Max.)	30fps (Max.)
Focus	Manual	Manual	Auto/ Manual	Auto/Manual	Auto/Manual
Shooting Area	A4 Landscape	A4 Landscape	320x240mm	360x270mm	310cmx233cm
Image Rotation	Camera Head 0°/ 90°/-90°	Camera Head 0°/ 90°/-90°	Camera Head 0°/ 90°/180°/270°	Electronic Rotation 0°/ 90°/180°/270°/360°	Electronic Rotation 0°/ 90°/180°/270°/360°
Image Effect : (Color/B&W/Negative/Mirror/Freeze)	Yes (With Reverse)	Yes (With Reverse)	Yes (With Reverse)	Yes	Yes
Image Adjustment	Auto/ Manual + Auto Image	Auto/ Manual + Auto Image	Auto/ Manual	Auto/ Manual	Auto/ Manual + Auto Image
White Balance & Exposure & Night View	-	Yes	-	Yes (With AVerPointer)	Yes
AVerPresenter (AVerBox/AVerVisor)	-	-	-	Yes (Horizontal)	Yes (Vertical & Horizontal)
Split Screen	-	-	-	Yes	Yes
Picture-in-Picture	-	-	-	Yes	Yes
Display Mode	Text/Graphics	Text/Graphics/High Frame	Text/Graphics/High Frame	Text/Graphics/High Frame/Microscope	Text/Graphics/High Frame/Microscope
Capture Mode	Single/Continuous	Single/Continuous	Single	Single	Single/Continuous
Image Storage & Backup	Built-in Memory (Max: 40)	Built-in Memory (Max: 80)	Built-in Memory (Max: 80)	Built-in Memory (Max: 80),SD Card Slot	Built-in Memory (Max: 80),SD Card Slot
Timer	Yes	Yes	Yes	Yes	Yes
Profile	-	Yes	-	-	Yes
Output	VGA/S-Video/Composite Video	VGA/S-Video/Composite Video	DVI/VGA/S-Video/Composite Video/RS-232 (With S-Video/RS-232 Adapter Cable)	DVI/VGA/S-Video/Composite Video/RS-232 (With S-Video/RS-232 Adapter Cable)	DVI/VGA/S-Video/Composite Video/RS-232
Input	VGA (15-Pins D-sub, Pass Through)	VGA (15-Pins D-sub, Pass Through)	VGA (15-Pins D-sub, Active Pass Through)	VGA (15-Pins D-sub, Pass Through)	VGA (15-Pins D-sub, Pass Through)
USB 2.0 Port	Yes	Yes	Yes	Yes	Yes
RJ-45 Port	-	-	-	-	-
Embedded LED Lamp	Yes	Yes	Attachable LED Lamp (With Laser Positioning Guide)	Yes (With Laser Positioning Guide)	Yes
Embedded Light Box	-	-	-	-	Yes (5"x4")
Remote Control	-	Yes	Yes	Yes	Yes (With Laser Pointer)
Carrying Bag	-	-	Yes	Yes	Yes (Dust Cover)
Dimension	Operating: 160mm x 170mm x 450mm Folded: 287.4mm x 232.5mm x 61mm	Operating: 160mm x 170mm x 450mm Folded: 287.4mm x 232.5mm x 61mm	Operating: 220mm x 1140mm x 500mm Folded: 365mm x 173.4mm x 95.85mm	Operating: 229mm x 429mm x 488mm Folded: 229mm x 508mm x 140mm	Operating: 480mm x 380mm x 505mm Folded: 480mm x 380mm x 150mm
Net Weight	2.4kg	2.4kg	2kg	3.8kg	7kg
Power Source	AC/DC 100-240V , 50-60 Hz	AC/DC 100-240V , 50-60 Hz	AC/DC 100-240V , 50-60 Hz	AC/DC 100-240V , 50-60 Hz	AC/DC 100-240V 3.33 , 50-60 Hz
Warranty	3-Year Limited Parts and Labor ^{*1}	3-Year Limited Parts and Labor ^{*1}	3-Year Limited Parts and Labor ^{*1}	3-Year Limited Parts and Labor ^{*1}	3-Year Limited Parts and Labor ^{*1}

* Subject to change without notice.

E-mail: office@primaryict.co.uk Tel: 01227 769 400 Fax: 01227 250 450

*1: 1-Year Limited Warranty is adopted for power adaptor, remote controller, light modular, light box and lamps.