



Gadget that Sets You Free
Wired Magazine Award
 February 2004



— DWL-P200

Power Over Ethernet Adapter

The DWL-P200 Power Over Ethernet (PoE) adapter is designed to supply operational power to surveillance cameras and wireless LAN devices such as access points, bridges and routers. It enable power current to travel on the Ethernet network cable, thus eliminates the need to directly connect a power supply to the wireless LAN device. The DWL-P200 supports both 5VDC and 12VDC power requirements. Power requirement can be selected through a DIP switch.

Facilitates Installation

The Power Over Ethernet allows you to install the wireless LAN device and surveillance camera at places such as on a building rooftop, on or near a ceiling, or other difficult places where power is not easily accessible. The idea is increase the usefulness of your camera and wireless LAN to provide connectivity to users regardless of their proximity to a power outlet or a network cable.

Data and DC Power Transmission on the Same Network Cable

On a standard UTP Category 5 cable, only two pairs (pins 1, 2, 3 and 6) are used for Ethernet data transfer. Power Over Ethernet is designed to take advantage of the unused pins of

the remaining pair of cable wires. Consequently, a single Category 5 cable will now carry both Ethernet data and DC power. The idea is to supply the remote end with power and the requirements of Ethernet connectivity via a single Cat 5 cable.

Base Unit and Terminal Unit

The DWL-P200 includes a base unit and a terminal unit. At one end, the base unit inserts DC voltage into the unused wires (pins 4, 5, 7 and 8) of the network cable. At the other end, the terminal unit splits the data and DC power apart. Data signals continue to travel on remaining network cables, while DC power is fed into the power adapter, which connects to an AC power outlet.

Key Features

- Provides DC power over existing Category 5 cable to wireless LAN device
- Cuts costs and provides convenience
- Transforms incoming AC power into low-voltage DC power
- 1 base unit and terminal unit provide power to 1 wireless LAN device
- Protects wireless LAN device from possible power-surges
- Supports both 5VDC and 12VDC power (selectable through a DIP switch)

DWL-P200

Technical Specifications

Power Over Ethernet Includes

- 1 base unit
- 1 terminal unit

Category 5 Pin Power Usage

- Data: pins 1, 2, 3, 6
- Power: pins 4, 5, 7, 8

Output Voltage

- Input: 48VDC, 400mA
- Output: 5VDC or 12VDC (DIP switch selectable)

Ethernet Cable

- Data rate: 10/100Mbps
- TIA/EIA 568 Cat. 5
- Connector: RJ-45

Dimensions

- Base unit: 81 x 52 x 28 mm
- Terminal unit: 81 x 52 x 28 mm

Operating Temperature

0° to 40 °C

Storage Temperature

-40° to 70 °C

Operating Humidity

10% to 80% RH

Storage Humidity

5% to 90% RH

EMI Certification

- FCC Part 15 Class B
- CE Class B

Power Adapter Safety Certifications

CSA International

Box Includes

- Power Over Ethernet base unit
- Power Over Ethernet terminal unit
- AC to DC power adapter
- DC power cable
- Quick Installation Guide
- Ethernet cable

Wireless LAN



Ordering Information

DWL-P200 Power Over Ethernet

Please specify your order as follows:

- DWL-P200/A** US standard power adapter
- DWL-P200/B** UK standard power adapter
- DWL-P200/E** EU standard power adapter
- DWL-P200/N** Australia standard power adapter
- DWL-P200/CN** China standard power adapter



Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-714-885-6000	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-022-652-6696	FAX: 91-022-652-8914
Middle East (Dubai)	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Latinamerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-55039320	FAX: 55-11-55039321
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299

Primary ICT Ltd www.primaryict.co.uk Tel: 01227 769 400 Fax: 01227 250 450 E-mail: office@primaryict.co.uk